


















		1NZ-FXE
cm ³ or CC (cu. in.)		1497 (91.4)
		11.0–15.0 (0.43–0.59) ※196–392
mm (in.)	N (kgf)	
	DENSO	SK16R11
	NGK	IFR5A11
	A	1.1 (0.043)
		8–12° (DLC3 Terminals 13 (TC) – 4 (CG) Connected)
BTDC		
		0.17–0.23 (0.007–0.009)
		0.27–0.33 (0.011–0.013)
w/cooling fan off		
		950–1050
rpm		
		0.5
		CO%



		588 (6.0, 85)
		392 (4.0, 57)
		100 (1.0, 14)
		59 (0.6, 8.5)
	2,500 rpm	150–550 (1.5–5.6, 22–80)
	A	29 (296, 21) 90° 90°
	B	20 (204, 15)
	C	27 (275, 20)


		1NZ-FXE
		3.4 (3.6, 3.0)
		3.7 (3.9, 3.3)
liter (US qts, Imp. qts)		API grade SJ "Energy-Conserving", SL "Energy-Conserving" or ILSAC* multigrade engine oil
		For gasoline engine *2 5.5 (5.8, 4.9) *3 5.3 (5.6, 4.7)
liter (US qts, Imp. qts)		For electric motor and inverter and Converter 2.7 (2.9, 2.4)




Prius


					
	A	138–148 (5.43–5.83)			
	B	1–4 (0.04–0.16)			
	C	 101.0 (3.98)	 103.7 (4.08)		
 mm (in.)		SAE J1703 or FMVSS No. 116 DOT3			
294 N (30 kgf, 66.1 lbf) 		6–9			
					
	A	 1.0 (0.039)			
mm (in.)	B	 20.0 (0.787)	7.5 (0.295)		
 mm (in.)		 1.0 (0.039)			
 mm (in.)		 174.0 (6.850)			

	NHW
 N·m (kgf-cm, ft-lbf)	216 (2200, 159)
 N·m (kgf-cm, ft-lbf)	103 (1050, 76)

	NHW
	3.6 (3.8, 3.2)
 liter (US qts, Imp. qts)	"Toyota Genuine ATF WS" or equivalent

	NHW
 mm (in.)	 30 (1.18)

			
	A	$-0^{\circ}35'\pm 45'$ ($-0.58^{\circ}\pm 0.75^{\circ}$)	$-1^{\circ}30'\pm 30'$ ($-1.5^{\circ}\pm 0.5^{\circ}$)
	B	$12^{\circ}35'\pm 45'$ ($12.58^{\circ}\pm 0.75^{\circ}$)	—
	C	$3^{\circ}10'\pm 45'$ ($3.17^{\circ}\pm 0.75^{\circ}$)	—
	D	$41^{\circ}\pm 2^{\circ}$	—
	F+G	$0^{\circ}\pm 12'$ ($0^{\circ}\pm 0.2^{\circ}$)	$0^{\circ}18'\pm 15'$ ($0.30^{\circ}\pm 0.25^{\circ}$)
	H-I mm (in.)	0 ± 2 (0 ± 0.08)	3 ± 2.5 (0.11 ± 0.10)

	km/h (mph)		
 kPa (kgf/cm ² or bar, psi)	195/55R16 87V	240 (2.4, 35)	230 (2.3, 33)
	195/60R15 88V		